

PEX Press

The Viega PEX Press system provides the industry's most comprehensive selection of PEX tubing, fittings and accessories. Viega's unique PEX Press fittings come with a factory assembled sleeve and enhanced flow through characteristics. Along with a wide variety of PEX fittings, Viega also offers the patented ManaBloc water distribution system which helps homeowners realize a reduction in water waste and increased energy savings.

FEATURES AND BENEFITS

- Available in Zero Lead bronze and polymer
- In sizes 5/16" to 2"
- Tool locator ring to ensure proper alignment of press tool
- Uses the same tools as other Viega press systems
- Proven quality
- Reduced flow noise
- Excellent chlorine resistance
- Comprehensive written warranty

CODES AND STANDARDS

- IPC: International Plumbing Code
- UPC: Uniform Plumbing Code
- NSPC: National Standard Plumbing Code
- CSA International: Canadian Standard Association
- NSF/ ANSI 61: Drinking Water System Components – Health Effects
- NSF/ ANSI 61G: Lead Content Evaluation Procedure to meet $\leq 0.25\%$ average lead content
- NSF/ ANSI 14: Plastics Piping System Components and Related Materials
- CSA B137.5: Standard Specification for PEX tubing systems in pressure applications
- ASTM F876: Standard Specification for PEX Tubing
- ASTM F877: Standard Specification for PEX Water Distribution System
- ASTM F1807/F2159: Standard Specification for PEX Insert Fittings
- ASTM F2023: Standard Test Method for Evaluating the Oxidative Resistance of Cross-linked Polyethylene PEX Tubing and Systems to Hot Chlorinated Water
- UL 1821: Thermoplastic Sprinkler Pipe and Fittings for Fire Protection Service

ZERO LEAD

References to Zero Lead throughout this publication means product meeting the requirements of NSF 61-G through testing under NSF/ ANSI Standard 372 (0.25% or less percent maximum weighted average lead content). A few states already require meeting those requirements for plumbing fittings used in cooking and drinking water systems and federal law taking effect January 1, 2014 will make the requirements applicable to all states.



**ViegaPEX Ultra Tubing
Zero Lead**

- PEX
- Straight length

Technical data

PEX designation code 5306
Chlorine resistance rating CL5
UV resistance 6 months

ASTM F876, ASTM F877

Model V5006.5

d	L [ft]	Version	Wt [lb]	Quantity	Part No	DG
½	10	blue	0.550	50	33629	1
½	20	blue	1.180	50	33620	1
¾	10	blue	0.550	25	33649	1
¾	20	blue	2.020	25	33645	1
1	20	blue	3.480	5	33651	1



**ViegaPEX Ultra Tubing
Zero Lead**

- For installation between studs
- PEX
- ManaPac

Components

Recycled plastic reels

Technical data

PEX designation code 5306
Chlorine resistance rating CL5
UV resistance 6 months

ASTM F876, ASTM F877

Model V5008

d	L [ft]	Reel(s)	Version	Wt [lb]	Quantity	Part No	DG
¾	500	2	red/blue	56.000	1	33300	1
¾	500	1	blue	28.000	1	33905	1
¾	500	1	red	28.000	1	33805	1
½	300	2	red/blue	48.000	1	33326	1
½	300	1	blue	23.100	1	33923	1
½	300	1	red	23.100	1	33823	1



**ViegaPEX Ultra Tubing
Zero Lead**

- PEX
- Coil

Technical data

PEX designation code 5306
Chlorine resistance rating CL5
UV resistance 6 months

ASTM F876, ASTM F877

Model V5007

d	L [ft]	Version	Wt [lb]	Quantity	Part No	DG
¾	500	white	21.000	1	32405	1
½	100	white	6.000	1	32421	1
½	300	white	17.100	1	32423	1
½	500	white	28.000	1	32425	1
½	1000	white	55.000	1	32420	1
¾	100	white	11.000	1	32441	1
¾	300	white	32.100	1	32443	1
¾	500	white	53.000	1	32445	1
1	100	white	17.000	1	32461	1
1	500	white	88.000	1	32465	1



**ViegaPEX Ultra Tubing
Zero Lead**

- PEX
- Straight length

Technical data

PEX designation code 5306
Chlorine resistance rating CL5
UV resistance 6 months

ASTM F876, ASTM F877

Model V5007.5

d	L [ft]	Version	Wt [lb]	Quantity	Part No	DG
½	10	white	0.550	50	33429	1
½	20	white	1.100	50	33420	1
¾	10	white	0.550	25	33459	1
¾	20	white	2.100	25	33405	1
1	20	white	3.480	5	33461	1



**ViegaPEX Ultra Tubing
Zero Lead**

- PEX
- Coil

Technical data

PEX designation code 5306
Chlorine resistance rating CL5
UV resistance 6 months

ASTM F876, ASTM F877

Model V5009

d	L [ft]	Version	Wt [lb]	Quantity	Part No	DG
¾	100	black	4.200	1	32701	1
¾	500	black	21.000	1	32705	1
½	100	black	5.500	1	32721	1
½	300	black	16.500	1	32723	1
½	500	black	29.000	1	32725	1
½	1000	black	55.000	1	32720	1

PEX Crimp

The Viega PEX Crimp system provides the industry's most comprehensive selection of PEX tubing, fittings and accessories. Along with a wide variety of PEX fittings, Viega also offers the patented ManaBloc water distribution system which helps homeowners realize a reduction in water waste and increased energy savings.

FEATURES AND BENEFITS

- Available in Eco brass and PolyAlloy
- In sizes 3/8" to 1"
- Proven quality
- Corrosion-resistant
- Reduced flow noise
- Excellent chlorine resistance
- Comprehensive written warranty

CODES AND STANDARDS

- IPC: International Plumbing Code
- UPC: Uniform Plumbing Code
- NSPC: National Standard Plumbing Code
- CSA International: Canadian Standard Association
- NSF/ ANSI 61: Drinking Water System Components – Health Effects
- NSF/ ANSI 61G: Lead Content Evaluation Procedure to meet $\leq 0.25\%$ average lead content
- NSF/ ANSI 14: Plastics Piping System Components and Related Materials
- CSA B137.5: Standard Specification for PEX tubing systems in pressure applications
- ASTM F876: Standard Specification for PEX Tubing
- ASTM F877: Standard Specification for PEX Water Distribution System
- ASTM F1807/F2159: Standard Specification for insert PEX Fittings
- ASTM F2023: Standard Test Method for Evaluating the Oxidative Resistance of Cross-linked Polyethylene PEX Tubing and Systems to Hot Chlorinated Water
- UL 1821: Thermoplastic Sprinkler Pipe and Fittings for Fire Protection Service

ZERO LEAD

References to Zero Lead throughout this publication means product meeting the requirements of NSF 61-G through testing under NSF/ ANSI Standard 372 (0.25% or less percent maximum weighted average lead content). A few states already require meeting those requirements for plumbing fittings used in cooking and drinking water systems and federal law taking effect January 1, 2014 will make the requirements applicable to all states.



**ViegaPEX Ultra Tubing
Zero Lead**

- PEX
- Straight length

Technical data

PEX designation code 5306
Chlorine resistance rating CL5
UV resistance 6 months

ASTM F876, ASTM F877

Model V5006.5

d	L [ft]	Version	Wt [lb]	Quantity	Part No	DG
1/2	10	blue	0.550	50	33629	1
1/2	20	blue	1.180	50	33620	1
3/4	10	blue	0.550	25	33649	1
3/4	20	blue	2.020	25	33645	1
1	20	blue	3.480	5	33651	1



**ViegaPEX Ultra Tubing
Zero Lead**

- For installation between studs
- PEX
- ManaPac

Components

Recycled plastic reels

Technical data

PEX designation code 5306
Chlorine resistance rating CL5
UV resistance 6 months

ASTM F876, ASTM F877

Model V5008

d	L [ft]	Reel(s)	Version	Wt [lb]	Quantity	Part No	DG
3/8	500	2	red/blue	56.000	1	33300	1
3/8	500	1	blue	28.000	1	33905	1
3/8	500	1	red	28.000	1	33805	1
1/2	300	2	red/blue	48.000	1	33326	1
1/2	300	1	blue	23.100	1	33923	1
1/2	300	1	red	23.100	1	33823	1



**ViegaPEX Ultra Tubing
Zero Lead**

- PEX
- Coil

Technical data

PEX designation code 5306
Chlorine resistance rating CL5
UV resistance 6 months

ASTM F876, ASTM F877

Model V5007

d	L [ft]	Version	Wt [lb]	Quantity	Part No	DG
3/8	500	white	21.000	1	32405	1
1/2	100	white	6.000	1	32421	1
1/2	300	white	17.100	1	32423	1
1/2	500	white	28.000	1	32425	1
1/2	1000	white	55.000	1	32420	1
3/4	100	white	11.000	1	32441	1
3/4	300	white	32.100	1	32443	1
3/4	500	white	53.000	1	32445	1
1	100	white	17.000	1	32461	1
1	500	white	88.000	1	32465	1



**ViegaPEX Ultra Tubing
Zero Lead**

- PEX
- Straight length

Technical data

PEX designation code 5306
Chlorine resistance rating CL5
UV resistance 6 months

ASTM F876, ASTM F877

Model V5007.5

d	L [ft]	Version	Wt [lb]	Quantity	Part No	DG
1/2	10	white	0.550	50	33429	1
1/2	20	white	1.100	50	33420	1
3/4	10	white	0.550	25	33459	1
3/4	20	white	2.100	25	33405	1
1	20	white	3.480	5	33461	1



**ViegaPEX Ultra Tubing
Zero Lead**

- PEX
- Coil

Technical data

PEX designation code 5306
Chlorine resistance rating CL5
UV resistance 6 months

ASTM F876, ASTM F877

Model V5009

d	L [ft]	Version	Wt [lb]	Quantity	Part No	DG
3/8	100	black	4.200	1	32701	1
3/8	500	black	21.000	1	32705	1
1/2	100	black	5.500	1	32721	1
1/2	300	black	16.500	1	32723	1
1/2	500	black	29.000	1	32725	1
1/2	1000	black	55.000	1	32720	1